



## Tridol<sup>C6</sup> S6 LT

Synthetic Aqueous Film-Forming Foam (AFFF) Concentrate

- Superior quality synthetic Aqueous Film-Forming Foam concentrate
- Provides a vapour suppressing foam blanket providing rapid control and extinguishment
- Use in high risk situations or where fast extinguishment is essential
- UL162 listed
- Use At 6% and is readily proportioned using conventional foam proportioning equipment – portable and fixed
- Compatible with air aspirating and non-aspirating discharge devices
- Suitable for use with fresh or sea water



Tridol<sup>C6</sup> S6 LT is a superior quality synthetic Aqueous Film-Forming Foam (AFFF) concentrate for extinguishing and securing flammable hydrocarbon liquid fires.

Tridol<sup>C6</sup> S6 LT is a unique combination of hydrocarbon and fluorochemical surface active agents. It produces a vapour-sealing aqueous film that spreads rapidly over the fuel surface to provide rapid control and extinguishment.

- Film-forming for fast flame knock down and extinguishment.
- Burnback resistance and post-fire security.
- Foam blanket reseals when ruptured by personnel or equipment.

### Applications

Tridol<sup>C6</sup> S6 LT is used in high risk situations where hydrocarbons (such as crude oil, gasoline, diesel fuel, and aviation kerosene) are stored, processed, or transported. It is used extensively on Rapid Intervention Vehicles (RIV) at major international airports and military bases where fast extinguishment with limited quantities of foam is essential for saving life. Other applications include hydrocarbon storage tanks, process areas, warehouses, road/rail loading racks, power stations, marine terminals, and offshore platforms.

Tridol<sup>C6</sup> S6 LT provides a vapour suppressing foam blanket on unignited hydrocarbon spills.

Tridol<sup>C6</sup> S6 LT can also be used as a wetting agent in combating fires in Class A materials such as wood and paper.

### Performance

The fire performance of Tridol<sup>C6</sup> S6 LT is measured primarily against internal test procedures.

### Approvals and Listings

Tridol<sup>C6</sup> S6 LT is independently tested and certified to EN1568:2008 part 3.

### Equipment

Tridol<sup>C6</sup> S6 LT is intended for use at 6% (6 parts concentrate to 94 parts water).

Tridol<sup>C6</sup> S6 LT is readily proportioned using conventional foam proportioning equipment such as portable and fixed (in-line) foam venturi proportioners, handline nozzles/branchpipes with pick-up tubes, balanced pressure variable flow proportioners, balanced pressure bladder tank proportioners, and around-the-pump proportioners.

Tridol<sup>C6</sup> S6 LT can be used with air aspirating discharge devices such as low expansion branchpipes, monitors, top pourer sets, rimseal foam pourers, foam/water sprinklers, and base (sub-surface) injection systems.

Tridol<sup>C6</sup> S6 LT can be used with non aspirating discharge devices such as spray/fog branchpipes and nozzles, monitors, and spray/fog sprinklers. However, non-aspirated application is not recommended as the primary method of attack for major fires where a stable foam cover is essential.

# Tridol<sup>®</sup> S6 LT

## Synthetic Aqueous Film-Forming Foam (AFFF) Concentrate

### Compatibility

Tridol<sup>®</sup> S6 LT is suitable for use in combination with:

- Soft or hard, fresh, brackish or sea water.
- Dry powder extinguishing agents either separately or as twin agent systems.
- Expanded protein-based or synthetic foams for application to a fire in sequence.

### Storage

Tridol<sup>®</sup> S6 LT is exceptionally stable in long-term storage. A shelf-life of at least ten years may be expected if it is stored properly.

### Environment & Disposal

As all 'C6' foams contain PFAS please refer to the product's Safety Data Sheet (SDS) and website for more information regarding the use, discharge and disposal of all firefighting foam products.

### Reliability

Tridol<sup>®</sup> S6 LT is produced to rigorous quality control standards to ensure consistent fire performance and excellent product reliability.

Angus Fire operates a quality management system which complies with the requirements of BS EN ISO 9001.

#### Typical Physico-Chemical Properties

Appearance		Amber Liquid
Specific gravity @ 20°C (68°F)		1.02 - 1.06
pH @ 20°C (68°F)		6.6 - 7.6
Viscosity @ 20°C (68°F)	mm <sup>2</sup> sec <sup>-1</sup>	2.9
Maximum continuous storage temperature	°C (°F)	49 (120)
Maximum intermittent storage temperature	°C (°F)	60 (140)
Freezing point	°C (°F)	-19 (-2.2)
Effect of freeze/thaw		No loss of performance
Lowest use temperature	°C (°F)	-15 (5)

#### Typical Foam Properties

Foam generated using the U.K. Defence Standard DEF42-40 5 lpm branchpipe at 7 Bar pressure.  
Foam collected in a 1630 ml N.F.P.A. drainage pan.

Expansion ratio		≥8:1
25% drainage time	min/sec	≥ 3'00"

#### Typical Packing Specification

	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Empty weight (kg)	1.2	0.8	9.0	9.0	70
Filled weight (kg)	27	21	217	225	1110
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H
Part number	FN0308GOP	FN0308TOP	FN0308JOP	FN0308WOP	FN0304L8



**EN1568:2008  
Part 3**

**EMERGENCY FOAM SERVICE** Call +44 (0) 15242 61166 – 24 hours a day, every day

#### GENERAL SALES

##### Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK  
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 261580

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire 5165C6/3 10/21  
Tridol<sup>®</sup> is a registered trademark of the Angus International group.